

PENTAX – CCTV & Industrial C or CS-mount lenses



MODEL	Focal length	Mount	Sensor ; aperture ; Working distance
H416 (KP)	4,2mm	C-mount	1/2" ; 1,6-C, WD 0,2m
H612A (KP)	6,0mm	C-mount	1/2" ; 1,2-C, WD 0,2m
H1212B (KP)	12,0mm	C-mount	1/2" ; 1,2 - 22, WD 0,2m
C418DX (KP)	4,8mm	C-mount	2/3" ; 1,8 - C, WD 0,3m
C815B (KP)	8,5mm	C-mount	2/3" ; 1,5 -C, WD 0,2m
C1614A (KP)	16,0mm	C-mount	2/3" ; 1,4 - 22, WD 0,3m
B1214D-2 (KP)	12,5mm	C-mount	1" ; 1,4 - C, WD 0,3m
B1218A (KP)	12,5mm	C-mount	1" ; 1,8 - C, WD 0,3m
B2514D (KP)	25,0mm	C-mount	1" ; 1,4 - 22, WD 0,3m
B2518 (KP)	25,0mm	C-mount	1" ; 1,8 - C, WD 0,6m
B5014A (KP)	50,0mm	C-mount	1" ; 1,4 - C, WD 1,0m
B7514C (KA)	75,0mm	C-mount	1" ; 1,4 - C, WD 1,2m
H614-M (KG)	6,0mm	C-mount	megapixel ; 1/2" ; 1,4-16 ; WD 0,2m
H1214-M (KP)	12,0mm	C-mount	megapixel ; 1/2" ; 1,4-17 ; WD 0,25m
C1614-M (KP)	16,0mm	C-mount	megapixel ; 2/3" ; 1,4-18 ; WD 0,25m
C2514-M (KP)	25,0mm	C-mount	megapixel ; 2/3" ; 1,4-19 ; WD 0,25m
C3516-M (KP)	35,0mm	C-mount	megapixel ; 2/3" ; 1,6-16 ; WD 0,4m
C5028-M (KP)	50,0mm	C-mount	megapixel ; 2/3" ; 2,8-22 ; WD 0,9m
C7528-M (KP)	75,0mm	C-mount	megapixel ; 2/3" ; 2,8-32 ; WD 0,7m
***	zoom lens	***	take contact with SDVision for more information
***	fixed focal	CS-mount	take contact with SDVision for more information

For more information please contact us at sales@sdvision.be